



# **Indigo™ Series** 322 Ice Cube Machine

ID-0322A IY-0324A D-0323W Model:

## Ice Machine Flectric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available)

## Minimum circuit ampacity:

Air-cooled: 11.5 1ph Water-cooled: 10.7 1ph

### Maximum fuse size:

Air-cooled: 15 amps Water-cooled: 15 amps

Indiao Series i-322

Ice Machine on B-320 Bin

## **Specifications**

### **BTU Per Hour:**

3,300 (average) 4,500 (peak)

#### Refrigerant:

R-404A CFC-free

## **Operating Limits:**

- Ambient Temperature Range: 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

☑ IY-0325W

- Space-Saving Design Up to 350 lbs. (159 kgs.) daily ice production and only 22" (55.88 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- DuraTech™ Exterior provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available LuminIce™ Growth Inhibitor controls the growth of bacteria and yeast within the foodzone.



# Ice Shape



**Half Dice** (.95 x 2.86 x 2.22 cm)



Dice ½" x ½" x ½" (2.22 x 2.22 x 2.22 cm)













COMPANY WITH QUALITY SYSTEM

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







# i-322 on B-320 Storage Bin 24.50" (62.23 cm) (A) Electrical Entrance (2) Options B 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) () 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units) (Water-Cooled Gints) (D) 1/2" (1.27 cm) Auxillary Base Drain Socket (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet F 1/2" (1.27 cm) F.P.T. Ice Making Water Drain © 3/4" (1.91 cm) Bin Drain 6.00" (15.24 cm) **Installation Note** 34.00" (86.30 cm) Minimum installation clearance: 22".00 (55.88 cm) Top/side: 12" (30.50 cm) Back is 5" (12.7 cm)

# Space-Saving Designs



	i-322 B-320	i-322 B-420	
Height	59.50" 151.13 cm	71.50" 181.61 cm	
Width	22.00" 55.88 cm	22.00" 55.88 cm	
Depth	34.00" 86.30 cm	34.00" 86.30 cm	
Bin Storage	210 lbs. 95 kgs.	310 lbs. 141 kgs.	

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

# Specifications

				Ice Production 24 Hours		Power Usage kWh/100 lbs.	Water Usage/100 lbs. 45.4 kgs. of Ice	ENERGY	
		Model	Ice Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	@90°Air/70°F	Potable Water	STAR*	
	AIR-COOLED	ID-0322A	dice	335 lbs.	225 lbs.	7.49	23.9 Gal.		
				152 kgs.	102 kgs.		90.5 L		
		IY-0324A half-	half-dice	350 lbs.	230 lbs.	7.32	23.9 Gal.		
				159 kgs.	104 kgs.		90.5 L		
	WATER-COOLED	ID-0323W	dice ()	330 lbs.	270 lbs.	6.19	23.9 Gal.	NA	
				150 kgs.	122 kgs.		90.5 L		
		IY-0325W half-dice	350 lbs.	290 lbs.	5.94	23.9 Gal.	NA		
				159 kgs.	132 kgs.	5.94	90.5 L	NA	
	Š	* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 193 gal/731 L.							

\* Water-cooled models are excluded from ENERGY STAR qualification.

Order ice storage bin separately.

## Accessories

#### LuminIce™ Growth Inhibitor reduces yeast and bacteria growth for a

cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



Arctic Pure®
Water Filters
Reduces
sediment and
chlorine odors for

better tasting ice.



AuCS® schedules and performs routine ice machine cleaning automatically.



4775E ©2014 Manitowoc 2/14 Continuing product improvement may necessitate change of specifications without notice.

2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com

